

## **Users manual MSB6-Premium Telescopic Mast**

### **Transport:**

- The Telescopic mast in Box is equipped with 4 lifting eyes
- Equipped with sleeves for transport with forklift

### **Users manual 4-piece telescopic mast in box (TM Box)**

Must be installed by a professional person.

For using the telescopic mast, see figure Exploded View

From windspeed more then 40 km/hrs slide the mast down complete into the box.

1. Before using, level the Telescopic mast in Box on a stable ground
2. Open the doorsize with the winch in front of you
3. Pull out the 4 stabilizers and slide out to the maximum size
4. Lock each stabilizer with the bolt inside, not possible to slide in/out
5. Turn out the wheel and level each stabilizer
6. Open both top covers for assembling the floodlight, camera, etc. on the T-part of the telescopic mast
7. Take care there is enough space for winching out/in during assembling the floodlights etc.
8. Check the cable position and the position of the steel wire.
9. The winch should rattle during hoisting.
10. Extend the mast to his maximum size until it automatical locks the inner mast (automatic lock in front of the mast)
11. To provide tolerance between the masts, turn the winch slightly forward until the stainless steel cable is in a tighten position.
12. Close and lock the 2 topcovers
13. Telescopic Box is ready for use

### **Lower the telescopic mast in box (slide in)**

- Open the frontdoor and both topcovers of the Telescopic mast in Box
- Unlock the automatic locker and slide gently down the inner mast until it drops completely inside the box
- Turn in the wheels and unlock the 4 stabilizers and slide them inside the box
- Close the topcovers and the door
- Check if everything is safe and ready for transport

Although composed with the utmost care, we can accept no liability for any damage caused by errors / omissions in the texts

